



TAPERED COUPLINGS

Manufactured in steel, the tapered coupling can be adapted on all gearbox referred below. The machining on CNC authorizes a perfect fitting, which will be checked using the Prussian blue.

Flange Ø	Gearbox type	Shaft Ø	Register Ø	Ø Hole pitch circle	No. & hole Ø	Reference
120	Yanmar	40	65 M	100	4 x 10	TOUKUH400
127	Hurth-BW-ZF	35	63.5 M	108	4 x 11.5	TOUKUJ350M
127	Hurth-BW-TD-ZF	40	63.5 M	108	4 x 11.5	TOUKUJ400M
127	Hurth-BW-TD-ZF	45	63.5 M	108	4 x 11.5	TOUKUJ450M
127	Hurth-BW-TD-ZF	50	63.5 M	108	4 x 11.5	TOUKUJ500M
146	PRM-Twin Disc-ZF	40	76.2 M	120.6	6 x 13.2	TOUKUN400M
146	PRM-Twin Disc-ZF	45	76.2 M	120.6	6 x 13.2	TOUKUN450M
146	PRM-Twin Disc-ZF	50	76.2 M	120.6	6 x 13.2	TOUKUN500M
146	PRM-Twin Disc-ZF	55	76.2 M	120.6	6 x 13.2	TOUKUN550M
146	PRM-Twin Disc-ZF	60	76.2 M	120.6	6 x 13.2	TOUKUN600M
146	Twin Disc-MPM	45	76.2 F	120.6	6 x 16.3	TOUKUN451M
146	Twin Disc-MPM	50	76.2 F	120.6	6 x 16.3	TOUKUN501M
146	Twin Disc-MPM	55	76.2 F	120.6	6 x 16.3	TOUKUN551M
146	Twin Disc-MPM	60	76.2 F	120.6	6 x 16.3	TOUKUN601M
184.15	Twin Disc	50	95.3 F	152.4	6 x 19.5	TOUKUS501M
184.15	Twin Disc	55	95.3 F	152.4	6 x 19.5	TOUKUS551M
184.15	Twin Disc	60	95.3 F	152.4	6 x 19.5	TOUKUS601M
184.15	Twin Disc	70	95.3 F	152.4	6 x 19.5	TOUKUS701M
184.15	Twin Disc	80	95.3 F	152.4	6 x 19.5	TOUKUS801M

 M / F: Male or Female
 Other dimensions on request